



ELEGANZA SOLANYA SOLEYA




OVER-GLASS AND UNDER-GLASS AWNINGS

The new over-glass and under-glass awnings SOLANYA and SOLEYA captivate due to their plain and linear structure. The small cassette of the SOLANYA with only 151 x 131 mm, can be mounted discreetly onto or beneath the terrace roof. Thanks to the small guide rails, roofs up to a surface of 20 m² can can be shaded easily and, above all,

in an aesthetically pleasing way. The larger box of the SOLEYA with 253×156 mm can provide shade to terraces up to a surface of 30 m². The design SOLEYA protect with side seam guiding is a seamless and wind resistant design model for a surface of up to 26 m^2 and with wind protection class 3.







- Over-glass and under-glass awning without side seam guiding
- Motor, rio motor
- Single installation, combination/linkage and in-line installation possible



SOLANYA 151 mm x 131 mm.



SOLANYA Front rail Max. sloping projection 4500 mm



SOLANYA Guide rail 30 x 52 mm

SOLEYA

| Limit sizes | SOLEYA | SOLEYA protect |
|-------------------------------|--------|----------------|
| Max. width in mm | 6000 | 6000 |
| Max. sloping projection in mm | 6500 | 6000 |
| Max. surface m ² | 30 | 26 |

- The big sister with optional side seam guide (protect)
- Double guide rain possible for over-glass option
- Single installation, combination/linkage and in-line installation possible
- As an option, LED can be integrated in the cassette profile and in the guide rails



SOLEYA 253 mm x 156 mm.



SOLEYA Front rail Max. sloping projection 6500 mm



SOLEYA Guide rail 55 x 77 mm Double guide rail 114 x 77 mm



PERGOLA AWNING

FI FGANZA

ELEGANZA is a new pergola awning with two columns and with brackets for wall mounting. In the design ELEGANZA protect, the cover is side seam guided. With the 253 x 156 mm cassette, terraces up to 3.4 m deep and 5.5m wide can be shaded. In addition, dimmable LED strips can be in-

tegrated in the guides and in the cassette of the pergola awning of up to 30 m² in size to provide the appropriate ambient light. An optional available Varioplus roller blind as vertical blind can be mounted between the columns as protection against the setting sun.



| Limit sizes | ELEGANZA | ELEGANZA protect |
|-------------------------------|----------|------------------|
| Max. width in mm | 6000 | 6000 |
| Max. sloping projection in mm | 5500 | 5500 |
| Max. surface m ² | 30 | 26 |

- The elegant pergola awning with optional side seam guide (protect)
- Optional single installation, combinations with double guide rail possible
- As an option, LED can be integrated in the cassette profile and in the guide rails
- Varioplus roller blind with motor between fixed columns optionally available
- Optionally available with crank handle provided at the lowerable column to ensure the lateral rainwater drainage
- Water drainage eyelets in the cover
- Range of inclination 0° -30°, recommended minimum inclination angle 14° to ensure the rainwater drainage with fixed columns
- Wall, ceiling and rafter brackets included



ELEGANZA 253 mm x 156 mm.



Optional Varioplus roller blind (motor operated)



LED in the box and the guidesELEGANZA and SOLEYA under-glass

